LISTING OF THE CLAIMS:

Claim 1. (Currently Amended) A laminate support used in the process of wire bonding a circuit device which is arranged on a substrate, comprising:

[a] said substrate having a first surface supporting said circuit device; and

a wire having a diameter positioned on said first surface of said substrate, said substrate including a closed woven mesh having a thickness of between about 2.5 and 4.0 mils and being essentially constituted of fiberglass having strands whose separation distance is equal to or less than said diameter of said wire on said first surface of said substrate, said separation distance of said strands being within the range of about 0.2 to 0.7 mils so as to substantially prevent deformation and collapse of said circuit device during said process of wire bonding.

Claims 2-5 (Cancelled).

Claim 6. (Original) The laminate support used in the process of wire bonding a circuit device in accordance with claim 1, wherein said circuit device is a pad of large scale integrated design.

Claim 7. (Currently Amended) A laminate support used in the process of wire bonding a circuit device which is arranged on a substrate, comprising:

[a] said substrate having a first surface supporting said circuit device; and

a wire having a thickness positioned on said first surface of said substrate, said substrate including a closed woven mesh having a thickness of between about 2.5 to 4.0 mils and being essentially constituted of fiberglass having warp and weave strands, whose separation distance is equal to or less than the thickness of said wire on said first surface of said substrate, as measured lengthwise through said closed woven mesh, said separation distance of said strands being within the range of about 0.2 to 0.7 mils so as to substantially prevent deformation and collapse of said circuit device during said process of wire bonding.

Claims 8-11 (Cancelled).

Claim 12. (Original) The laminate support used in the process of wire bonding a circuit device in accordance with claim 7, wherein said circuit device comprises a pad of large scale integrated design.